



OPREMA ZA DALJINSKI VIDEO NADZOR - BNS MONITOR

B.N.S. MONITOR d.o.o

VS-101 1-ch video server (ACTi modul)

Cijena po Jedinici (komad): 1 .996,25 kn; (ukljuèen
PDV)



MPEG-4 Advanced Simple Profile is able to deliver DVD resolution video at lower data rates and smaller file sizes. Video server already built-in Bi-directional Audio function. Digital TimeCode Embedded. Offer MPEG-4 D1 resolution 720x576, providing sharper image. The intelligent network System On a Chip (SoC) solution delivering high performance and QoS (802.1pQ) for ensuring a stable and high quality video streaming (IP multicast, IGMP supported). Built-in LAN and WAN (PPoE supported) ports. DDNS supported. Simultaneously analog and digital outputs. Live video variation setting-Brightness, Contrast, Hue and Saturation. MPEG-4 Living Streaming-protocols supported by TCP/IP, UDP, HTTP, BOOTP, DHCP, PPPoE. Dual MPEG-4 video stream output via LAN/WAN (PPPoE supported) ports at the same time. QoS Function setting-Priority service scheduling. Authorization setting-The system supervisor can set authorization to prevent unauthorized user. Offer max. 10 user password management. Offer multilingual operation interface. Motion Detection-Customization motion detection windows, The maximum is up to 3 windows. Hardware and software Watch Dog.



Resolution	QCIF 176x144, CIF 352x288, D1 720x576
Image FPS	25fps at full D1 resolution PAL
Network	RJ-45x2
Ethernet system	10/100base-T x 2 for LAN/WAN
Protocol supported	TCP/IP, UDP, HTTP, ARP, PPPoE, DDNS, IGMP
Qos	Layer 2, 3
Simultaneous Access	Unlimited (multicast)
WAN	WAN for FTTP, Cable modem or x DSL connectivity
Video Decoder	Two analog preprocessing channels in differential CONS style for best S/N-performance Standard ITU 656 YUV 4:2:2 format (8-bit) on VPO output bus. CCIR-601 and CCIR-656 YUV 4:2:2 progressive or interlace
MPEG-4 Encoder	MPEG-4 Advanced Simple Profile @L3 plus FGS (Fine Granularity scalability) NTSC: 720x480 @ 30fps PAL: 720x576 BNC 25fps
Video input	1.0Vp-p, 75ohms BNC connector
Video output	1.0Vp-p, 75ohms BNC connector
Audio input	8kHz, Mono PCM / Unbalanced, 1.4Vp-p, 1Vrms
Audio output	8kHz, Mono PCM / Unbalanced, 1.4Vp-p, 1Vrms
Remote control	Rs485 : half duplex
Software	Web: Microsoft Internet Explorer 6.0 or above ActiveX kontrola 16 channel AP software
Power Supply	DC12V /1.5A
Power Consumption	7.5W
Operation Temp	5 C ~ 50 C

[Informacije o dobavljaèu](#)