



OPREMA ZA DALJINSKI VIDEO NADZOR - BNS MONITOR

B.N.S. MONITOR d.o.o

IP-7142 Vanjska dan/noć; WDR IP kamera

Cijena po Jedinici (komad): 5 .016,25 kn; (uključèn
PDV)

IP7142 Vanjska dan/noć; WDR kamera

Predstavljamo Vam prvu vanjsku dan/noćnu kameru IP7142, opremljena WDR (wide dynamic range) CMOS senzorom, može se nositi s bilo kojim vanjskim svjetlosnim uvjetima. Dizajnirana je za vanjski 24 satni video nadzor. IP7142 kamera ima mogućnost dan/noć snimanja kao i anti-vandal funkcije koje korisnik može lako postaviti u IP nadzornom sistemu bez posebnih dodataka. S pomičnim IR-cut filterom i ugrađenim IR osvjetljivačem (snop svjetla i do 15 m), automatsko uključivanje IR filtera i uključivanje IR osvjetljivača omogućava kvalitetnu sliku u noćnim uvjetima. Meanwhile, the IP66-rated integrated housing shields this camera from dust and water, allowing it to be applied in harsh weather conditions of outdoor environments. IP7142 with WDR(Wide dynamic range) feature can be very helpful to cope with very challenging lighting conditions. It is capable of capturing both of the dark part and bright part and combining the differences into a scene to generate a highly realistic image as original scene. Because it preserves as much information in the video as possible, IP7142 helps provide video quality closer to the capabilities of the human eye. Consequently, it is largely applied in highly contrast environments such as lobby entrances, parking lots, ATM, loading areas and much more. Incorporating numbers of advanced features including simultaneous dual streams, 3GPP mobile surveillance, 802.3af compliant PoE, two-way audio by SIP protocol, RS-485 interface for scanners or pan/tilts driver connection, and HTTPS encrypted data transmission. VIVOTEK IP7142 allows users to boost your robust IP surveillance system by reproducing clear images in proper color in extreme high-contrast environments for your indoor/outdoor security and monitoring applications.

Namjenski aplikacije primjene kamere: Daljinski video nadzor lokacija i snimanje putem Interneta (WAN) Lokalni video nadzor lokacija i snimanje putem lokalne mreže (LAN) Slanje E-MAIL poruke sa slikom po alarmnom događaju ili detekciji kretanja **Potrebna oprema:** PC - pregled u živo sa kamere preko Internet Explorera PC sa priloženim programom uz kameru za pregled u živo i snimanje do 32 kamere na različitim lokacijama 3G mobitel za pregled u živo

Specifikacija:

Wide Dynamic Range CMOS Sensor 3.3~12mm Vari-focal Board objektiv sa Auto-Iris objektivom Pomični IR-cut Filter za dan/noć funkciju Ugrađeni IR osvjetljivač dometa do 15 Metara IP66-standard kućišta za sve vremenske uvjete Real-time MPEG-4 and MJPEG Compression (Dual Codec) Podrška Dvostruki tok istovremeno Ugrađeni 802.3af kompatibilan PoE (Power over Ethernet) Dvosmjerni Audio sa SIP Protokolom Digitalni I/O za vanjske senzor ili alarm RS-485 Interfejs za PAN/TILT skener

Pogled:

Konektori:

Garancija 2 godine

[Informacije o dobavljaču](#)